


Item <b>12.0K-A1</b>	Product Description				Payment		30% IN ADVANCE BALANCE BEFORE SHIPMENT		DELIVERY TIME	
	Single Rated Line Pull	Motor	Control	Gear Train	e	CE	pack size	FOB		
	12000 lbs. (5443 kgs. )	6.0hp/4.5kw, Series Wound 24VDC	Remote switch, 12' (3.7m) lead	3-Stage Planetary	Pack Type	Case	cm	Ningbo	25	
	Gear Reduction Ratio	284: 1	Clutch	Sliding Ring Gear	Carton	1/CTN	65*19*47			
	Brake Action	Automatic in-the-drum	Drum Size	Diameter 2.5inch(64mm), Length 8.82inch(224mm. )						
	Cable	diameter (27m of 9.5mm )	Fairlead	4-way roller fairlead						
	Recommended Battery	650 CCA minimum for winching	Battery Leads	2 gauge, 72inch (1.83m)						
	Finish	Black	Weight:	N. W. (30kgs), G. W. (34kgs)						
	Winch overall Dimens(LxWxH)	21.3" x 6.3" x 8.6"(630mmX185mmX270mm)								
	Line pull LBS.<Kgs>	line speed FPM.<MPM>	Motor current Amps	Layer of cable						Total Rope on Drmt Ft<M>
	0<0>	21.3<6.50>	65	1						12000<5440>
	2000<907>	11.5<3.50>	126	2						9210<4170>
	4000<1814>	9.4<2.85>	175	3						8030<3640>
	6000<2722>	7.9<2.40>	230	4						4694<3125>
	10000<4532>	5.8<1.75>	355							
	12000<5440>	4.4<1.35>	400							

